



Flag Pole Set Parts



< Post 1 - Top
30" long
small hole
2" down,
with insert



< Post 2
2nd from Top
30" long
small hole
8" down,
with insert



< Post 3
3rd from Top
30" long
no hole,
with insert

< Post 4
Bottom
30" long
no hole,
no insert

**NOTE:
HALF-STAFF
USAGE:**

Simply put
post 3 at top,
then use posts
1 and 2 to hold
the flag.

Take care that
flag doesn't
touch ground
or shrubs.

Caution:
Please take down
flag pole in winds
of 25 mph or more.

10' Flag Pole Set Assembly Instructions

Flag Pole:

<Slide parts together as shown at far left.
It is important that the correct sequence
is followed for pole assembly.

Ground Socket Installation:

IMPORTANT!

- 1. Create a PILOT HOLE!**
(1" in diameter
by 10-12" deep)
- Position socket over the pilot hole
and push halfway down.
- Test for straightness by
inserting flag pole section.
- Hammer down until socket top
is level with surface.


Slide flag pole into socket.
Remove for easy mowing.

Important!
To Avoid damage to Ground Socket!
Do not use a hammer without wooden
block (i.e.: 2 x 4).
Never use the pole to hammer socket
into hole!
Always make a pilot hole to assure
that the soil is clear of rocks!

Ground Socket Relocation Tips:

Should the need arise
to relocate your flag,
remove pole and dig
6-8" deep and 4 inches
around the socket.

This will allow for an
easier pullout.



Post 3 to Top

Flag Pole Posts and Inserts may be shipped separately,
requiring insert-to-pole assembly:

**3 Inserts are supplied,
to be used at bottom
of Posts 1,2 & 3.**

